



NUMBER OF CONTACTS	A	B	C	D
9	±0.25	±0.13	±0.38	±0.25
15	16.33	24.99	30.85	19.28
25	24.66	33.32	39.14	27.65
37	38.38	47.04	53.04	41.30
	54.84	63.50	69.32	57.44

SPECIFICATIONS:
ELECTRICAL SPECIFICATION

Contact Current Rating: 3 Amperes
 Dielectric Withstanding Voltage:
 AC 1000/60ses.r.m.s.
 Insulation Resistance:
 5000 Megohms MINIMUM at DC 500V
 Contact Resistance:25 MilliOhms Maximum
 Operating Temperature:-55°c_+105°c
MECHANICAL CHARACTERISTICS:
 Contact Insertion Force: 300gf/Max
 Contact Separation Force:25gf Min
MATERIALS:
 Contacts:Brass
 Insulator:-PBT +30%(UL94V-0)
 Shell:Steel

DBS XXS G X X X
 Type
 No of contact
 Female
 Gold plated
 Metal shell:
 N : Nickel/Tin plated
 T : Tin plated only
 Thickness of gold plated
 1 : Gold flash
 2 : 3u" 5 : 15u"
 3 : 5u" 6 : 20u"
 4 : 10u" 7 : 30u"

Third angle projection

General Dimension Tolerance

	X ±	.X ±0.30
	.XX ±0.15	
	.XXX ±0.08	

Rev	Description/Date	Drawn By: Storm.li	Customer:
△		Checked By:Simmon	Part No.:
△		Approved By: Tony	Title:
SGS Report No.:			

DBS-XXS-G-X-X-X
 D-SUB P.C.B. SOLDER
 FEMALE TYPE
SOUTH SEA TERMINAL CO.,LTD