



SPECIFICATION

- * Voltage Rating : 50V DC Max.
- * Current Rating : 0.5A Max.
- * Operating Temperature : -20°C ~ +80°C
- * Insulation Resistance : 1000 M Ω Min.
- * Contact Resistance : 100 M Ω Max.
- * Switch Type : Open & Close

SOLDERABILITY

- * Vaporphase : 215°C 30 sec. Max.
- * IR Reflow : 230°C 10~15 sec. Max.
- * Manual Soldering : 360°C 3 sec. Max.

MATERIAL

- * BASE : PA-9T UL 94V-0
- * COVER : PA-9T UL 94V-0
- * CONTACT : COPPER ALLOY

FINISH

- * CONTACT : TIN / GOLD PLATER

1	2	3	4	5	6	7	8	9	10	11	12	13	14
Rev	Description/Date	Drawn By: Storm.li	Customer:	Part No.:	SCC Low Profile Sliding SMT Type	Third angle projection	Units: mm						
△	MODIFY DRAWING 01/29/2004	Checked By: Simmon		V-S36-S	General Dimension Tolerance	XX ±0.30	KXX ±0.20	XXXX ±0.10					
△		Approved By: Tony	Title:										
SGS Report No.:													

SOUTH SEA TERMINAL CO., LTD